

## TRACTOR SAFETY QUIZ

The correct answer for each of the following statements is TRUE or FALSE.  
Please mark your selection.

- |   |   |  |
|---|---|--|
| T | F | 1. Refueling an engine presents no danger if it is shut off.   |
| T | F | 2. To inspect for leaks in hydraulic lines, run your hands over the hoses.   |
| T | F | 3. Always shut off the engine and apply the parking brake before dismounting the tractor.                          |
| T | F | 4. All PTO shafts should be guarded with the proper shielding.   |
| T | F | 5. Tractors may be started safely only from the operator's seat.   |
| T | F | 6. Noise levels of 100 decibels on a tractor are considered safe for an 8 hour exposure.                           |
| T | F | 7. When traveling, the front-end loader should be positioned high for good visibility.                             |
| T | F | 8. Weights help keep the front end of the tractor down.  |
| T | F | 9. Proper training is essential for safe tractor operation.  |
| T | F | 10. Tractor upsets are a leading cause of tractor fatalities.  |
| T | F | 11. It is alright to drill holes in a ROPS frame to mount a CB radio.  |
| T | F | 12. Hitch pins should always have proper safety catches to prevent accidental unhitching.                          |
| T | F | 13. When towing a load, go down the hill in the same gear as you would go up a hill.                               |
| T | F | 14. It is not necessary to use a seat belt when the ROPS is built into the cab.                                    |
| T | F | 15. When driving your tractor on the roadway, you must have a slow-moving vehicle sign on the rear of the tractor. |
| T | F | 16. Be sure the highway is clear of traffic before pulling into it.  |
| T | F | 17. When towing equipment on the highway, you must have a proper safety chain hook-up.                             |
| T | F | 18. When pulling a load up a slope, keep the hitch as high as possible.  |
| T | F | 19. When stuck in the mud, try to back out first.  |
| T | F | 20. The position of a tractor's loader changes the center of gravity as the position of the loader changes.        |
| T | F | 21. Three is the <b>maximum</b> number of riders allowed on a tractor.   |
| T | F | 22. If you are working with a tractor with rollover protection, always wear your seatbelt.                         |
| T | F | 23. Always read the operator's manual before operating a new tractor.  |
| T | F | 24. If tractor stability becomes uncertain on a slope, turn downhill.  |
| T | F | 25. Check your tires and wheels for proper pressure and tread regularly.   |